



DESCRIPTION

The PSMFxxBL/CBL Series is a transient voltage suppressor array, designed to protect applications such as consumer electronic products, automotive, telecommunications, aerospace and intelligent control systems. This series is available in both unidirectional and bidirectional configurations. This series is rated for 200 Watts peak pulse power (10/1000 μ s) and is offered in a space saving SOD-123FL package. The PSMFxxBL series meets IEC 61000-4-2 (ESD) and IEC 61000-4-4 (EFT) requirements.

FEATURES

- Compatible with IEC 61000-4-2 (ESD): Air \pm 15kV, Contact \pm 8kV
- Compatible with IEC 61000-4-4 (EFT): 40A, 5/50ns
- Compatible with IEC 61000-4-5 (Surge): 8/20 μ s Waveform
- 200 Watts Peak Pulse Power per Line (tp = 10/1000 μ s)
- Low Inductance
- Excellent Clamping Capability
- Unidirectional & Bidirectional Configurations
- Low Leakage Current: < 1 μ A (Typical)
- Fast Response Time
- Available in Multiple Voltages
- RoHS Compliant
- REACH Compliant


APPLICATIONS

- Consumer Electronics
- Automotive
- Telecommunications
- Aerospace
- Intelligent Control Systems

MECHANICAL CHARACTERISTICS

- Molded SOD-123FL Package
- Approximate Weight: 0.0136 grams
- Lead-Free Pure-Tin Plating (Annealed)
- Solder Reflow Temperature:
Pure-Tin - Sn, 100: 260-270°C
- 12mm Tape and Reel Per EIA Standard 481
- Flammability Rating UL 94V-0

PIN CONFIGURATIONS



TYPICAL DEVICE CHARACTERISTICS

RTCA DO-160G COMPLIANT PRODUCT

MAXIMUM RATINGS @ 25°C Unless Otherwise Specified

PARAMETER	SYMBOL	VALUE	UNITS
Operating Temperature	T_J	-55 to 150	°C
Storage Temperature	T_{STG}	-55 to 150	°C
Steady State Power Dissipation at $T_L = 75^\circ\text{C}$	$P_{M(AV)}$	2.8	W
Peak Pulse Power ($t_p = 10/1000\mu\text{s}$) - See Figure 1	P_{PP}	200	Watts
Maximum Instantaneous Forward Voltage at 20A	V_F	5.0	V
Typical Thermal Resistance Junction to Lead	RJL	100	°C/W
Typical Thermal Resistance Junction to Ambient	RJA	220	°C/W

ELECTRICAL CHARACTERISTICS PER LINE @ 25°C Unless Otherwise Specified

PART NUMBER (See Note 1-3)	DEVICE MARKING		REVERSE STAND-OFF VOLTAGE V_{RWM} VOLTS	BREAKDOWN VOLTAGE $V_{(BR)} @ I_T$ VOLTS		TEST CURRENT @ I_T mA	MAXIMUM CLAMPING VOLTAGE (Fig. 2) @ I_P V_C VOLTS	MAXIMUM REVERSE SURGE CURRENT @ I_{PP} AMPS	MAXIMUM REVERSE LEAKAGE CURRENT @ V_{RWM} I_R μA
	UNI	BI		MIN	MAX				
PSMF6.0BL	KG	KGC	6.0	6.67	7.37	10	10.3	19.4	100
PSMF6.5BL	KK	KKC	6.5	7.22	7.98	10	11.2	17.9	30
PSMF12BL	LE	LEC	12.0	13.30	14.70	1	19.9	10.1	1
PSMF13BL	LG	LGC	13.0	14.40	15.90	1	21.5	9.3	1
PSMF15BL	LM	LMC	15.0	16.70	18.50	1	24.4	8.2	1
PSMF24BL	LZ	LZC	24.0	26.7	29.5	1	38.9	5.1	1
PSMF28BL	MG	MGC	28.0	31.1	34.4	1	45.4	4.4	1
PSMF30BL	MK	MKC	30.0	33.30	36.80	1	48.4	4.1	1
PSMF36BL	MP	MPC	36.0	40.00	44.20	1	58.1	3.4	1
PSMF58BL	NG	NGC	58.0	64.40	71.20	1	93.6	2.1	1

NOTE

1. Add a 'CBL' specify a bidirectional device; i.e., "PSMF6.0CBL".
2. Consult factory for other voltages.

FIGURE 1
PEAK PULSE POWER VS PULSE TIME




FIGURE 2
PULSE WAVEFORM





FIGURE 3
POWER DERATING CURVE



PACKAGE INFORMATION


RTCA DO-160G COMPLIANT PRODUCT

OUTLINE DIMENSIONS

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	2.60	3.00	0.102	0.118
B	1.60	2.00	0.063	0.079
C	3.45	3.95	0.136	0.156
D	0.10	0.25	0.004	0.010
E	0.30	0.90	0.012	0.035
F	0.80	1.20	0.031	0.047
G	0.95	1.35	0.037	0.053

NOTES

1. Dimensioning and tolerances per ANSI Y14.M, 1985.
2. Controlling dimension: millimeters.
3. Dimensions are exclusive of mold flash and metal burrs.




PAD LAYOUT DIMENSIONS

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	1.30		0.051	
B		1.70		0.067
C	1.30		0.051	


NOTES

1. Controlling dimension: millimeters



TAPE AND REEL

RTCA DO-160G COMPLIANT PRODUCT



SPECIFICATIONS

REEL DIA.	TAPE WIDTH	A0	B0	K0	D	E	F	W	P0	P2	P	tmax
178mm (7")	8mm	1.95 ± 0.3	3.95 ± 0.3	1.40 ± 0.05	1.55 ± 0.10	1.75 ± 0.20	3.50 ± 0.5	8.00 ± 0.20	4.00 ± 0.20	2.00 ± 0.2	4.00 ± 0.20	0.25

NOTES

1. Dimensions are in millimeters.
2. Surface mount product is taped and reeled in accordance with EIA-481.
3. Empty pocket between sprocket holes.
4. Suffix - T73 = 7" Reel - 3,000 pieces per 8mm tape.
5. Marking on Part - marking code (see page 2) and polarity band.

ORDERING INFORMATION

BASE PART NUMBER (xx = Voltage)	LEADFREE SUFFIX	TAPE SUFFIX	QTY/REEL	REEL SIZE	TUBE QTY
PSMFxxBL/CBL	N/A	-T73	3,000	7"	N/A

This device is only available in a Lead-Free configuration.

COMPANY INFORMATION**RTCA DO-160G COMPLIANT PRODUCT****COMPANY PROFILE**

In business more than 25 years, ProTek Devices™ is a privately held semiconductor company. The company offers a product line of overvoltage protection and overcurrent protection components. These include transient voltage suppressor array (TVS arrays) avalanche breakdown diode, steering diode TVS array and electronics SMD chip fuses. These components deliver circuit protection in electronic systems from numerous overvoltage and overcurrent events. They include lightning; electrostatic discharge (ESD); nuclear electromagnetic pulses (NEMP); inductive switching; and electromagnetic interference (EMI) / radio frequency interference (RFI). ProTek Devices also offers LED wafer die for ESD protection and related high frequency products. ProTek Devices is ISO 9001:2015 certified.

CONTACT US**Corporate Headquarters**

2929 South Fair Lane
Tempe, Arizona 85282
USA

By Telephone

General: 602-431-8101
Sales: & Marketing: 602-414-5109
Customer Service: 602-414-5114
Product Technical Support: 602-414-5107

By Fax

General: 602-431-2288

By E-mail:

Asia Sales: asiasales@protekdevices.com
Europe Sales: europesales@protekdevices.com
U.S. Sales: ussales@protekdevices.com
Distributor Sales: distysales@protekdevices.com
Customer Service: service@protekdevices.com
Technical Support: support@protekdevices.com

ProTek Devices (Asia Pacific) Pte. Ltd.

8 Ubi Road 2, #06-19
Zervex
Singapore - 408538
Tel: +65-67488312
Fax: +65-67488313

Web

www.protekdevices.com

COPYRIGHT © ProTek Devices 2019 - This literature is subject to all applicable copyright laws and is not for resale in any manner.

SPECIFICATIONS: ProTek reserves the right to change the electrical and or mechanical characteristics described herein without notice.

DESIGN CHANGES: ProTek reserves the right to discontinue product lines without notice and that the final judgement concerning selection and specifications is the buyer's and that in furnishing engineering and technical assistance. ProTek assumes no responsibility with respect to the selection or specifications of such products. ProTek makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ProTek assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability without limitation special, consequential or incidental damages.

LIFE SUPPORT POLICY: ProTek Devices products are not authorized for use in life support systems without written consent from the factory.